

Acoustical Underlayment for

CERAZORB Green

Ceramic Tile & Wood Underlayment

Ceramic Tile & Floated or Glue Down Hardwood

CeraZorb Green is a specially formulated rubber base underlayment that can be installed under both Ceramic Tile and Hardwood flooring. CeraZorb Green is a green product made from 92% recycled post consumer waste. CeraZorb Green is thin, only 3 mm thick and is easily bonded to concrete or wood sub floor. CeraZorb Green has been TCA tested and approved for use in residential & multi-family spaces.



CeraZorb Green allows developers/owners to choose to install tile or hardwood using the same underlayment.

Acoustical Testing

Model	Roll Size/ SF / Weight roll	IIC Wood Frame Const (floated hardwood)	Δ IIC 6" concrete slab (floated hard- wood)	Δ IIC 6" concrete slab (glue down hard- wood)	IIC 6" concrete slab with ceiling below - (glue down hardwood)	Δ IIC 6" concrete slab (Ceramic Tile)	IIC 6" concrete slab (Ceramic Tile)
CZG-3	4' x 30' 120 sf roll 60 lbs roll	IIC 57	Δ IIC 21	Δ IIC 19	IIC 60	Δ IIC 20	IIC 49

Product Specifications



 92% Recycled Content

Density ASTM D-792	43 # Cubic FT
Tensile (Machine Direction) ASTM D-412	75 PSI
Elongation at Break ASTM D-412	55%
Compression (100 PSI) ASTM F-36	20-40%
Hardness A Shore Durometer ASTM D-2240	40-55
Tear Strength ASTM D624, Die C	25 PPI
Flexibility Factor ASTM F147	1

WARRANTY

Impacta Underlayments will remain responsible for the performance / consistent quality as long as they have been installed according to the written instructions supplied by Sound Seal and in situations where the specific Impacta model is meant to be installed. Sound Seal warranties that spillage of casual water onto a finished floor with CeraZorb Green installed will have no effect on the performance of the CeraZorb Green. Any liability for sub-sequential damages is not accepted. The sound reducing capabilities of Impacta underlayments have been tested under laboratory conditions and therefore may differ in other situations.



50 H.P. Almgren Drive | Agawam, MA 01001
Tel. 800.569.1294 | Fax 413.789.2248
www.impactaunderlayments.com | impacta@soundseal.com

